

SPECIFICATION

产品规格书

FPE PART NO. :

DM3416A-600L

DESCRIPTION:

Wire Wound Type Common Mode Filter



广东美信科技股份有限公司

GUANGDONG MISUN TECHNOLOGY
CO., LTD

TEL: (86)769-86761589 86762589

FAX: (86)769-86761549

广东省东莞市企石镇新南金湖一路 3 号

No.3, Jinhu 1st Road, Xinnan, Qishi Town,
Dongguan City, Guangdong Province

为电磁赋能，创工业至美

Enable electromagnetism, Create ultimate beauty

FPE APPROVAL

(公司承认章)



DRAWN BY:

Jingwei XU

CHECKED BY:

Junmao Zhang

APPROVAL BY:





Angus Shi

1. 特征 Features

- ◆ High common mode impedance at high frequency Effects excellent noise suppression performance
- ◆ 100% Lead(Pb) & Halogen-Free and RoHS compliant.
- ◆ Operating temperature -40~+105°C
- ◆ FOR LAN Module application/ Compatible with 1G Base-T
- ◆ Supports up to 15W POE applications



2. 外形尺寸 Dimension



SUGGEST LAYOUT


(Steel plate thickness 0.1mm Typ)

Dimensions in mm


A	B	C	D1	D2	E
3.4±0.20	1.6±0.20	2.0±0.20	0.66±0.10	0.64±0.10	0.20 REF

3. 电性规格 Specification

Part Number	Inductance(uH) [100kHz/0.1V] Min.	DC Resistance (Ω)Max.	Capacitance (pF)Max	Rated Current (mA)Max.	Rated Volt. (Vdc)	Withstand Volt. (Vdc) Max.	IR(Ω) Min.
DM3416A-600L	60	1.8	15	200	50	125	10M




4. 电路图 Schematic Diagram




5. 测量电路 Measurement Circuits 2Line

Common mode




Differential mode



6. 材料 Materials

No.	Description	Specification
a.	Upper Plate	Ferrite
b.	Core	Ferrite Core
c.	Termination	Ag/Ni/Sn
d.	Wire	Enameled Copper Wire



7. 样品测试数据 Sample Test Data

SAMPLE TEST DATA								
PARAMETER:	OCL	OCL	DCR	DCR	CP	CP	Vdc	IR
UNIT:	uH	uH	Ω	Ω	pF	pF	V	Ω
CONDITION:	100kHz/0.1V	100kHz/0.1V	DC	DC	100kHz/0.1V	100kHz/0.1V	DC	DC
PIN NO.:	1-2	4-3	1-2	4-3	1-4	2-3	1-4	1-4
MAX SPEC.:			1.80	1.80	15.0	15.0		
MIN SPEC.:	60.0	60.0					125	10M
AVERAGE =	82.2	82.1	0.98	0.98	11.74	11.68	-	-
STD DEV =	0.6	0.6	0.0	0.0	0.3	0.2	-	-
MAX =	83.2	82.8	0.99	0.99	12.22	11.98	-	-
MIN =	81.3	81.2	0.98	0.98	11.29	11.27	-	-
Max spec for 1.33 Cpk			1.00	1.00	12.9	12.4	-	-
Min spec for 1.33 Cpk	79.8	79.8					-	-
Cpk for Max spec			65.65	79.18	3.8	5.9	-	-
Cpk for Min spec	12.6	13.0					-	-
DATA								
1	82.48	82.63	0.98	0.99	11.75	11.73	PASS	PASS
2	81.74	81.69	0.98	0.98	12.10	11.70	PASS	PASS
3	82.56	81.25	0.98	0.99	12.22	11.98	PASS	PASS
4	82.85	82.83	0.98	0.99	11.46	11.91	PASS	PASS
5	81.36	81.19	0.98	0.98	11.91	11.57	PASS	PASS
6	81.92	82.38	0.98	0.98	11.79	11.58	PASS	PASS
7	83.18	82.26	0.99	0.98	11.29	11.27	PASS	PASS
8	82.27	82.16	0.98	0.99	11.42	11.71	PASS	PASS
9	81.88	81.62	0.99	0.98	11.86	11.72	PASS	PASS
10	81.31	82.67	0.99	0.98	11.65	11.58	PASS	PASS

8. 可靠性和试验条件 Reliability and Test Condition

序号	试验项目	参考标准	试验条件	判断依据	结果判定
1	可焊性	J-STD-002	8 小时蒸汽老化, 助焊剂类型: ROL0, 温度: 245℃。时间: 2.5s	1. 试验前后外观无可见物理性异常; 2. 端子表面焊锡覆盖率大于 95%。	PASS
2	低温	IEC-68-2-1	温度: -40℃, 持续时间: 96h。	1. 试验前后外观无可见物理性异常; 2. 电性能满足规格书要求。	PASS
3	高温	IEC-68-2-2	温度: 125℃, 持续时间: 96h。	1. 试验前后外观无可见物理性异常; 2. 电性能满足规格书要求。	PASS
4	振动	MIL-STD-202 method 204	加速度: 10g; 频率: 10~55~10 Hz; 12 个周期: 方向: 3 (X、Y、Z) 个方向, 每个方向 20 分钟 ;	1. 试验前后外观无可见物理性异常; 2. 电性能满足规格书要求。	PASS
5	跌落	IEC68-2-32	高度: 1000mm; 位置: 一角、三棱、六面 (共 10 次)	1. 试验前后外观无可见物理性异常; 2. 电性能满足规格书要求。	PASS
6	推力	GB/T16512 方法 Ua1	对器件侧面均衡施加 10N 作用力, 保持 60s	1. 试验前后外观无可见物理性异常; 2. 电性能满足规格书要求。	PASS
7	盐雾	EIA-364-26B ITEM B	盐雾浓度: 5%± 1%, pH 值: 6.5~7.2; 试验温度: 35℃, 时间: 16h:	1. 试验前后外观无可见物理性异常。 2. 试验后无明显生锈产生等不良现象。	PASS
8	耐焊接热	J-STD-002	回流焊三次, 峰值温度: 260℃。	1. 试验前后外观无可见物理性异常; 2. 电性能满足规格书要求。	PASS
9	湿热	IEC68-2-67	温度: 40℃, 相对湿度: 95%RH, 持续时间: 96h。	1. 试验前后外观无可见物理性异常; 2. 电性能满足规格书要求。	PASS
10	冷热冲击	IEC68-2-67	低温: -55℃, 高温: 125℃, 持续时间: 15min; 温度转换时间: ≤5min; 循环数: 100	1. 试验前后外观无可见物理性异常; 2. 电性能满足规格书要求。	PASS

9. 焊接和安装 Soldering and Mounting

9-1. Soldering

Mildly activated rosin fluxes are preferred. FPE terminations are suitable for all wave and re-flow soldering systems. If hand soldering cannot be avoided, the preferred technique is the utilization of hot air soldering tools.


9-1.1 Solder re-flow:

Recommended temperature profiles for re-flow soldering in Figure 1.

9-1.2 Soldering Iron(Figure 2):


Products attachment with a soldering iron is discouraged due to the inherent process control limitations. In the event that a soldering iron must be employed the following precautions are recommended.

- Preheat circuit and products to 150°C
- Never contact the ceramic with the iron tip
- Use a 20 watt soldering iron with tip diameter of 1.0mm
- 350°C tip temperature (max)
- 1.0mm tip diameter (max)
- Limit soldering time to 4~5 sec.



Reflow times: 3 times max.

Fig.1




Iron Soldering times: 1 times max.

Fig.2


10. 包装信息 Packaging Information

10-1. Reel Dimension



Type	A(mm)	B(mm)	C(mm)	D(mm)	E(mm)	H(mm)
13"x8mm	330±2	87±1	2.7±0.5	100±1	1.9±0.2	8±0.5


10-2. Tape Dimension / 8mm




W(mm)	E(mm)	F(mm)	P0(mm)	P2(mm)	P(mm)	DO(mm)	t(mm)	B0(mm)	A0(mm)	K0(mm)
8.00±0.10	1.75±0.10	3.50±0.10	4.00±0.10	2.00±0.10	4.00±0.10	1.50±0.10	0.25±0.05	3.60±0.10	1.88±0.10	2.30±0.10

10-3. Packaging Quantity

Chip/Reel	Carton
7000	70000



10-4. Tearing Off Force



The force for tearing off cover tape is 15 to 85 grams in the arrow direction under the following conditions.

Room Temp. (°C)	Room Humidity (%)	Room atm (hPa)	Tearing Speed mm/min
5~35	45~85	860~1060	300

Application Notice

Storage Conditions

To maintain the solderability of terminal electrodes:

1. FPE products meet IPC/JEDEC J-STD-020D standard-MSL, level 1.
2. Temperature and humidity conditions: Less than 40°C and 60% RH.
3. Recommended products should be used within 12 months from the time of delivery.
4. The packaging material should be kept where no chlorine or sulfur exists in the air.

Transportation

1. Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
2. The use of tweezers or vacuum pick up is strongly recommended for individual components.
3. Bulk handling should ensure that abrasion and mechanical shock are minimized.