

	Doc. No.	SP-A0162-02	Page No.	1/8
	Date Issued	2024-07-30	Prepared by	AShu
	Date revised	2024-07-30	Checked by	Sangshen
Product Specification	Rev. No.	A0	Approved by	Willy
Title : Board to Board Pitch 0.4mm X1270 Series Connector				

1. SCOPE (适用范围)

This specification covers the performance, tests and quality requirements for the Board to Board 0.40mm Connector.(本规范涵盖了 Board to Board 0.40mm 连接器的性能、测试和质量要求。)

2. PRODUCT DESCRIPTION (产品描述)

DESCRIPTION (描述)	Part Number (料号)
Housing 胶壳	X1270H1-2x25-PTV01
	X1270H2-2xXX-PTV01
	X1270H-2xXXAB-PTAuSn
	X1270H-2xXXA-PTAuSn
	X1270H-2xXX-PTV01
	X1270HA2-2xXXA-PTAuN
	X1270HI-2xXX-PTV01
Wafer 针座	X1270WVS-2xXXC-6TV01
	X1270WVS-2xXXC-PTV01
	X1270WR-2xXXA2-6TV01
	X1270WR-2xXXA-6TV01
	X1270WR-2xXXB-6TV01
	X1270WR-2xXXC-6TV01
	X1270WV-2xXXA2-6TV01
	X1270WV-2xXXA-6TV01
	X1270WV-2xXXB1-9TXX
	X1270WV-2xXXB-6TV01
	X1270WV-2xXXC-6TV01
	X1270WVS-2xXXA2-6TXX
	X1270WVS-2xXXA-6TV01
	X1270WVS-2xXXB1-9TAuSn
	X1270WVS-2xXXB1-9TXX
	X1270WVS-2xXXB-6TV01

3. APPLICABLE DOCUMENT (适用文件)

The following documents form a part of this specification to the extent specified herein. In the event of conflict between the requirements of this specification and the product drawing, the product drawing shall take precedence. In the event of conflict between the requirements of this specification and the referenced documents, this specification shall take precedence.(XKB Connection 下列文件构成本规范的一部分，在此规定的范围内。本规范要求与产品图纸有冲突

	Doc. No.	SP-A0162-02	Page No.	2/8
	Date Issued	2024-07-30	Prepared by	AShu
	Date revised	2024-07-30	Checked by	Sangshen
Product Specification	Rev. No.	A0	Approved by	Willy
Title : Board to Board Pitch 0.4mm X1270 Series Connector				

时，以产品图纸为准。如果本规范的要求与参考文件发生冲突，应以本规范为准。）

- MIL-STD-1344A Test method for electrical connector（电子连接器测试方法）
- MIL-STD-202F Test method for electrical components（电子零件测试方法）
- EIA364 Test method for electrical components（电子零件测试方法）
- JIS C0051 Test method for electrical components（电子零件测试方法）
- MIL-G-45204C Specification for gold plating（镀金规格）
- IEC-512-3 IEC standard for current carrying capacity tests（IEC 电流测试标准）
- QQ-N-290A Specification for nickel plating（镀镍规格）
- MIL-P-81728A Specification for tin/lead plating（镀锡铅规格）
- MIL-T-10727B Specification for tin plating（镀锡规格）
- UL498 UL standard for safety of attachment plug and receptacle（UL 安规要求标准）
- EN/ISO5961 Determination of total lead & cadmium content（总铅和总镉含量测定）
- EN1122 Determination of total lead & cadmium content（总铅和总镉含量测定）
- EN13346 Determination of heavy metals content（重金属含量测定）
- EPA3052 Determination of total lead & cadmium content（总铅和总镉含量测定）

4. REQUIREMENTS（XKB CONNECTION 要求）

4.1. Design and Structure（设计和结构）

Product shall be of the design, structure and physical dimensions specified on the applicable product drawing.（XKB Connection 产品的设计、结构和物理尺寸参考所适用的产品图纸）

4.2. Materials/ Finish（材料/表面处理）

Materials used in the structure of product shall be as specified on the applicable product drawing.（产品结构中使用的材料参考所适用的产品图纸）

4.3. Ratings（额定功率）

XKB Connection Item (项目)	Standard (标准)	
Rated Voltage (Maximum)额定电压	250V	AC
Rated Current (Maximum)额定电流	1A	
Operating temperature range工作温度范围	-40℃~+125℃ From -40 to +125 degree centigrade	

4.4. PACKAGING（包装）

Please refer to the packing drawing. 请参考产品包装图纸

	Doc. No.	SP-A0162-02	Page No.	3/8
	Date Issued	2024-07-30	Prepared by	AShu
	Date revised	2024-07-30	Checked by	Sangshen
Product Specification	Rev. No.	A0	Approved by	Willy
Title : Board to Board Pitch 0.4mm X1270 Series Connector				

5. TEST STANDARD (测试标准)

Unless otherwise specified, the standard range of atmospheric conditions for making measurements and tests are as follows (除另有说明外，用以进行测量和测试的标准环境条件范围如下)

- 5.1 Ambient temperature (环境温度) : 5℃ to 35℃
- 5.2 Relative humidity (相对湿度) : 45% to 85%
- 5.3 Air pressure (气压) : 86Kpa to 106Kpa

6. HOWEVER, IF DOUBTS ARISE CONCERNING JUDGMENTS. PERFORM UNDER THE FOLLOWING STANDARD CONDITIONS. (如果对判决产生疑问，按照下列标准条件执行)

- Temperature (温度) : 23±1℃.
- Humidity (湿度) : 50%±2% RH.
- Air Pressure (气压) : 86~106kPa

7. PERFORMANCE AND TEST DESCRIPTION (性能和测试类型)

7.1 APPRARANCE (外观)

ITEM	DESCRIPTION (类型)	TEST CONDITION (测试条件)	REQUIREMENT (要求)
1	Appearance (外观)	Visual. (目视)	Should not have any flaw Scratch discoloration and crushed (无任何裂痕、刮伤、 污染和变形)

7.2 ELECTRICAL (电气)

ITEM	DESCRIPTION (类型)	TEST CONDITION (测试条件)	REQUIREMENT (要求)
1	Low Level Contact Resistance (接触电阻)	EIA 364-23 Subject mated contacts assembled in housing to closed circuit of 100 mA max. at open circuit voltage of 20 mV max. (在开路最大电流 100mA 电压 20 mV 最 大下测量)	Iniital:20mΩ max (初始: 20 mΩ 最大)

	Doc. No.	SP-A0162-02	Page No.	4/8
	Date Issued	2024-07-30	Prepared by	AShu
	Date revised	2024-07-30	Checked by	Sangshen
Product Specification	Rev. No.	A0	Approved by	Willy
Title : Board to Board Pitch 0.4mm X1270 Series Connector				

2	Insulation Resistance (绝缘电阻)	MIL-STD-202, Method 302,Condition B Apply 250±10% volts DC between adjacent terminal or ground 。(分别在相邻端子或壳体之间施加 250V±10% DC 的电压持续 1 分钟)	1000 MΩ min
3	Dielectric Withstanding Voltage (耐电压)	MIL-STD-202, Method 301. Apply 100 Volts AC(RMS) between adjacent terminal or ground. Leakage current: 1mA Max. (分别在相邻端子或壳体之间施加 100V AC 1mA 的电流持续 1 分钟, 最大漏电电流 1mA)	No Breakdown (没有损坏)

7.3 MECHANICAL (机械)

ITEM	DESCRIPTION (类型)	TEST CONDITION (测试条件)	REQUIREMENT (要求)
1	Insertion Force(插入力)	EIA364-13 Insertion and withdrawal speed : 25mm/minute. (以每分钟 25mm 的速度沿轴向插入母座测量其插入力)	3~30N *Pin Max.
2	Extraction Force (拔出力)	EIA364-13 Insertion and withdrawal speed : 25mm/minute.以每分钟 25mm 的速度沿轴向从母座拔出测量其拔出力)	3~30N *Pin Min.
3	Durability (寿命测试)	EIA 364-09 Mate and Unmated connector for 15 cycles (沿轴向插拔 15 次)	Meets requirements of product appearance. Contact Resistance: 100 mΩ Max. after testing (符合产品外观要求, 测试后接触阻抗不大于 100mΩ)

	Doc. No.	SP-A0162-02	Page No.	5/8
	Date Issued	2024-07-30	Prepared by	AShu
	Date revised	2024-07-30	Checked by	Sangshen
Product Specification	Rev. No.	A0	Approved by	Willy
Title : Board to Board Pitch 0.4mm X1270 Series Connector				

4	Vibration Sinusoidal Low Frequency (低频正弦振动)	MIL-STD-202, Method 201. Subject mated connector to 10-55-10 Hz traversed in 1 minute at 1.5 mm amplitude 2 hours each of 3 mutually perpendicular plane, 10 mA. (对测试样品,在频率变化每分钟从10-55-10 Hz , 振幅 1.5 mm 条件下, 在互相垂直的三个面上, 每个面 2 小时下测量, 电流 10 mA)	No electrical discontinuity greater than 1 μ sec (s) shall occur. Contact resistance:100 mΩ max. (不能超过 1 微秒瞬间断开, 接触阻抗: 100 mΩ 最大)
5	Mechanical Shock (机械冲击)	MIL-STD-202, Method 213 No discontinuities of 1 μS or longer duration when mated connectors are subjected to 490m/s2 half-sine shock pulses. Three shocks in each direction applied along three mutually shocks. (将对插后的连接器固定于冲击实验机上, 中断不得大于或等于 1 μ s, 施加 490m/s2 半正弦脉冲波, 沿 3 个互相垂直达的方向冲击)	Appearance (外观): No Damage (没有损坏) Discontinuity (断讯): 1 μ sec maximum. (不能超过 1 微秒)

7.4 ENVIRONMENTAL (环境)

ITEM	DESCRIPTION (类型)	TEST CONDITION (测试条件)	REQUIREMENT (要求)
1	Thermal Shock (冷热冲击)	MIL-STD-202, Method 107D, condition A. Temperature range from -35°C to +85°C .Start from -35°C, after 30 min. change to +85°C; change time is no more than 30 seconds. Total 5 cycles. (温度变化范围: -40 ° C~ +125° C; 从 -40° C 开始, 30 分钟后换到+125° C; 转换时间不超过 30 秒; 共 5 个循环。)	No damage, Contact Resistance 100 mΩ max. (外观无损坏, 接触阻抗: 100 mΩ 最大)

	Doc. No.	SP-A0162-02	Page No.	6/8
	Date Issued	2024-07-30	Prepared by	AShu
	Date revised	2024-07-30	Checked by	Sangshen
Product Specification	Rev. No.	A0	Approved by	Willy
Title : Board to Board Pitch 0.4mm X1270 Series Connector				

2	Humidity (恒温恒湿)	MIL-STD-202, Method 103 Temperature (温度) :40±2°C Relative Humidity (相对湿度) : 90-95%; Duration (时间) :96 Hours	No damage, Contact Resistance 100 mΩ max.. Dielectric Strength should be OK. Insulation Resistance 1000MΩ min. (产品无损坏, 接触阻抗: 100 mΩ 最大; 耐电压测试 OK, 绝缘阻抗 1000MΩ 最小)
3	Solder ability (可焊性)	Immerse the solder pin of the connector in solder bath at 255±5°C for 3±0.5sec. After dipped the pin in the flux 5sec. (将端子脚浸入助焊剂中 5 秒, 然后将端子脚浸入 255±5°C 的锡炉中 3±0.5 秒)	Solder wetting: 95% of immersed area must show voids, Pin holes. (锡附着的面积应超过浸入表面积的 95%以上)
4	High temperature (高温)	MIL-STD-202, Method 108. Subject product to 125±2°C for 96 hours Continuously. (产品置于 125 ± 2° C 连续 96 小时)	Contact resistance: 120m Ω max. (接触阻抗 100 mΩ max.)
5	Salt Spray (盐雾)	MIL-STD-202, Method 101 Condition B. Connectors to 35+/-2°C. Humidity:85%(R.H). PH value:6.5~7.2 and 5+/-1% salt condition for 24hours. After test, rinse the sample with water and recondition the room temperature for 1 hour test CR and IR. (将连接器放置在 35±2°C, 温度为 85% PH 值 6.5~7.2 和 5%浓度的实验箱内测试 24 小时, 测试后用水清洗样品, 放置室温 1 小时测试接触阻抗与绝缘阻抗)	Appearance: No Damage (外观无损坏) Contact Resistance 100 mΩ Max. (接触阻抗(末态) 100 mΩ Max.)

	Doc. No.	SP-A0162-02	Page No.	7/8
	Date Issued	2024-07-30	Prepared by	AShu
	Date revised	2024-07-30	Checked by	Sangshen
Product Specification	Rev. No.	A0	Approved by	Willy
Title : Board to Board Pitch 0.4mm X1270 Series Connector				

6	Resistance to Soldering heat (焊锡耐热性)	The contact of terminal shall be tested resistance to soldering heat in the following conditions. After Resistance to soldering heat test Contact Resistance. (端子应在下列条件下做耐吃锡性试验, 焊锡耐热性后试接触阻抗) In case of solder iron (2 time) 电烙铁(两次) Temperature 温度: ≤350℃ Time 时间: 5s+/-1s	Should not have any flaw scratch and crack. (无任何裂痕、刮伤和破裂)
7	IR-reflow (回流焊)	MIL-STD-202G method 210F Peak temperature time 260℃ Max, 10 sec or more. (峰值温度时间最高 260℃, 10 秒或以上) Duration : 2 cycles (过炉 2 次) Lead-Free Solder (无铅锡膏): Sn96.5Ag3Cu0.5 Refer to section 9 (请参阅第 9 条)	Should not have any flaw scratch and crack (无任何裂痕、刮伤和破裂) No visual damage to insulator. (绝缘体不得有严重变形)

